

#### February, 2015

# 3M™ Performance Yellow Masking Tape 301+

## **Product Description**

3M™ Performance Yellow Masking Tape 301+ is an industrial strength yellow colored smooth crepe paper masking tape for paint masking, holding, bundling, and identifying applications.

#### **Product Features**

- Industrial-strength performance masking tape used for paint masking, bundling, holding, and identifying applications.
- 3M proprietary solvent-free adhesive sticks with confidence to most surfaces including metal, rubber, glass, and plastic while removing cleanly in one piece.
- Strong yellow crepe-paper backing conforms to irregular surfaces, resists bleed through from most industrial paint systems, and improves visibility during the paint masking process.
- Great paint lines.
- Temperature resistant up to 225°F (107°C) for 30 minutes.
- Offered in bulk and individually wrapped rolls.



## 3M™ Performance Yellow Masking Tape 301+

## **Technical Information Note**

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

## **Typical Physical Properties**

Property	Values		Method
Color	Yellow		
Total Tape Thickness	0.16 mm	6.3 mil	ASTM D3652
Backing	Smooth crepe paper		
Adhesive	Rubber		

## **Typical Performance Characteristics**

Property	Values		Method	Substrate
Peel Adhesion	3.3 N/cm	30 oz/in	ASTM D3330	Stainless Steel
Tensile Strength	38.5 N/cm	352 oz/in	ASTM D3759	
Elongation at Break	12 %		ASTM D3759	
Temperature Use Range	30 minutes up to 107 °C	30 minutes up to 225 °F		

### **Available Sizes**

Property	Values	
Standard Roll Length	55 m	60 yd

### 3M™ Performance Yellow Masking Tape 301+

### Storage and Shelf Life

Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton. To obtain best performance, use within 18 months from date of manufacture.

#### **Trademarks**

3M is a trademark of 3M Company.

#### References

## Safety Data Sheet (SDS)

https://www.3m.com/3M/en\_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en\_US&co=ptn&q=301+

#### **ISO Statement**

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

#### **Technical Information**

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

#### **Product Selection and Use**

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

#### Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

### **Limitation of Liability**

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

